

teleskopy.pl



Robust roof binoculars in an area with hunting and "birdish" parameters of 8.5x50. Good coatings on all optics (MC on objectives and eyepieces, phase coverage on prisms) are a guarantee of the reproduction and clarity of images obtained. High resistance to weather conditions (O-rings and nitrogen filling) and resistance to mechanical damage (rubberizing) ensure the longevity of the binoculars. Includes a neck strap, lenses covers and glasses, and a carrying case with a belt

Technical parameters

- â€¢ Lens diameter: 50 mm
- â€¢ Zoom: 8,5x
- â€¢ Exit pupil: 5.9 mm
- â€¢ Construction prisms: roof
- â€¢ Optical system: 8 elements in 6 groups
- â€¢ Material of glass elements: Optical glass Bak-4
- â€¢ Field of view: 98 m / 1000 m
- â€¢ Retracting the output pupil: 15 mm
- â€¢ Minimum distance of observation: 2.5 m
- â€¢ Twilight factor: 20.6
- â€¢ Adjusting for eye defect: +/- 4 D
- â€¢ The scope of adjustment of the spacing of pupils: 55 - 73 mm
- â€¢ Eyecups: adjustable, twist-up type
- â€¢ Waterproof: yes, up to 1 m to 30 minutes
- â€¢ Anti-reflective layers: FMC (Fully Multi-Coated), PhC (Phase Coating - phase coatings on prisms)
- â€¢ Dimensions: 165 x 133 x 60 mm
- â€¢ Weight: 870 g

Usage astronomy hunting planes nature scenery Warranty 5 years